



Years Warranty*

ANSMANN ALCT 6-24/2

Lead acid charger for 6V/12V/24V lead acid, SLA batteries

Features

- Lead acid charger for 6V/12V/24V lead acid, SLA batteries
- With the help of high-quality pole terminals a fast and reliable contact of lead acid batteries is possible
- Automatic voltage identification / Autosensing
- Clear LED display - easy to use
- Adjustable charging current
- Automatic REFRESH mode, if the battery is completely discharged
- Selectable COLD TEMP mode at cold temperatures
- Faulty cell detection
- Protection against short-circuit, wrong polarity and overcharge
- Automatic start of recharge, if the battery is left connected to the charger
- Ideal maintenance of lead acid batteries during winter time - no deep discharge
- Power and charging cable each 200cm
- Protected against dirt and water jets thanks to IP65



Voltage



Charging current



Overload protection



REFRESH Mode



COLD TEMP Mode



Cable length



Article number: 1001-0016
 Product content: ALCT 6-24/2 with pole terminals, power cord 2,0m, manual
 Customs tariff number: 85044055900
 Packing Unit: 4 (293 × 230 × 145 mm)
 Price: 49,99 €



Specifications

Input voltage	230V AC
Max. output current	2 A
Battery voltage	6 V / 12 V / 24 V
Output	6V: 0.5A 12V: 0.5A / 1A / 2A 24V: 1A
suitable for	Lead Acid / SLA
Overload protection	Yes
Automatic voltage detection	Yes
Charge current control	Yes
Color	black
Packaging	cardboard box
Storage temperature	-25 - 70 °C
Operating temperature	0 - 25 °C