



ANSMANN Energy 16 plus

Years Warranty*

Charging and maintenance device for 1-12 Micro AAA / Mignon AA, 1-6 Baby C / Mono D and 1-2 9V E-Block rechargeable batteries, automatic refreshing function, 2 USB charging sockets

Features

- Charging station for 1-12 Micro AAA, Mignon AA / 1-6 Baby C, Mono D / 1 -2 9V E-Block NiMH/NiCd rechargeable batteries; incl. 2 USB charging sockets
- Suitable for NiMH/NiCd rechargeable batteries
- Capacity quick test of the inserted cells
- Auto-diagnosis of the inserted cells with automatic start of a pre-charging and/or refreshing process, if required; tired cells will be activated
- Fast charging
- Microprocessor controlled charging & individual supervision of each cell position
- Battery-full detection (-dV) & automatic switch to trickle charge
- Multiple over charging protection
- Faulty cell & alkaline battery detection
- Easiest handling due to fully automatic control
- Clear indicators and controls for each charging



Individually controlled



Overcharging protection (trickle charge)



Refresh



Defect detection



Capacity Quick Test



Article number: 1001-0004
 Product content: Energy 16 plus, power cord 1,8m, manual
 Customs tariff number: 85044055900
 Packing Unit: 4 (355 × 305 × 310 mm)



Specifications

Input voltage	100 - 240V AC
For worldwide use	Yes
Chargeable cell chemistry	Nickel metal hydride
Chargeable cells	AAA / HR03 / AA / HR6 / C / HR14 / D / HR20 / 9V block / 6F22 / USB
Charging current AAA	400mA (1-12)
Charging current AA	1000mA (1-12)
Charging current C	1000mA (1-6)
Charging current D	1000mA (1-6)
Charging current E	60mA (1-2)
Charging current USB	1000mA (1-2)
Microprocessor control	Yes
Temperature monitoring	Yes
Safety timer	Yes
Single shaft monitoring	Yes
Overload protection	Yes
Refresh function	Yes
Battery defect detection	Yes
Kapazitäts-Schnelltest	Yes
Color	silver / blue
Packaging	cardboard box
Operating temperature	0 - 25 °C
Storage temperature	-25 - 70 °C