

# Products Specification

## 14.8V 5.0A Li-ion battery charger

SPECIFICATION		PREPARE	CHECK	APPROVE
MODEL:	PU-1396	Rain	Steven	Wilstar
ISSUE DATE:	2008-2-8			
COMMON/UNITE	DOC.NO:		REV: 1.0	PAGE:1 OF 1

### Smart 2-Stages Li-ion Battery charger

	ITEM	UNIT	SPECIFICATION	REMARK
<b>INPUT</b>				
01	Rating Input Voltage	V ac	100~240Vac 50-60Hz	
02	Input voltage range	V ac	90~264Vac	
03	Rating Input Current	A	0.6Arms	220Vac
04	Max.input power	W	100.0W	
<b>OUTPUT</b>				
05	Rating output voltage	V dc	16.8V	
06	Output voltage range	V dc	0VDC~16.8VDC	
07	Suit with Battery type		14.8V Li-ion battery charger and capacity>5000mAh	
08	Charging current(stage1)	A	5.0±0.5	
09	Charging voltage(stage2)	V	16.6-17.0V	
10	Cut-off current(stage1→2)	A	0.4-0.6A	
11	Typical charging time	hour	Fast charge 2hours Slow charge 5hours	
12	Max.output power	W	84.0W	
13	Hold-on time	ms	NC	Input:220Vac Output:Full load
14	Ripple current	mA	100	Input:220Vac Output:Full load
15	Charge finish condition		I<0.6A	
16	LED color		Red:charging Green:finish/idle	
17	Output protect	-	OCP&OVP&Polarity error protection	
18	Efficiency	%	80%(Typical)	At max.load
<b>Environment</b>				
19	Operate temperature	℃	0~+40	Full load&natural convection
20	Operate humidity	%RH	20~90	Relative humidity,non-condensin
21	Storage temperature	℃	-40~+70	
22	Storage humidity	%RH	10~95	Relative humidity,non-condensin
23	Cooling	-	Fan force cooling	
24	Temperature factor	%	--	
25	Vibration resistance		5MM/50HZ/600S	Non-operating condition.
26	Impact resistance		1 meter drop test>=3 times	Non-operating condition.
<b>Mechanical</b>				
27	Weight	g	450	
28	Size	mm	152.5*63.0*45.0	Casing only
29	Connectors	-	Defined when order	
<b>Safety</b>				
30	Max.temperature rise	℃	<40 on casing	At any line and Max.Load
31	Safety standards	-	CE(EN60335-2-29)	
32	EMC standard	-	CE(EN55014)	
33	MTBF	hrs	40000	
34	Limited power source	VA	-	
35	ESD	Kv	8.0	
36	Hi-Pot Insulation	v	Input to Output:3000Vac(1 min.)	For final nuit,cut-off current=10m



