

Products Specification

37.0V 6.0A Li-ion battery charger				
SPECIFICATION		PREPARE	CHECK	APPROVE
MODEL:	PU-1399	Rain	Steven	Wilstar
ISSUE DATE:	08/02/2008			
COMMON/UNITE	DOC.NO:		REV: 1.0	PAGE:1 OF 1
Smart 2-Stages Li-ion Battery charger				
	ITEM	UNIT	SPECIFICATION	REMARK
INPUT				
01	Rating Input Voltage	V ac	200~240Vac 50-60Hz	
02	Input voltage range	V ac	180~264Vac	
03	Rating Input Current	A	1.5Arms	220Vac
04	Max.input power	W	260.0W	
OUTPUT				
05	Rating output voltage	V dc	42.0V	
06	Output voltage range	V dc	0VDC~42.0VDC	
07	Suit with Battery type		37.0V Li-ion battery charger and capacity>5000mAh	
08	Charging current(stage1)	A	5.5~6.5	
09	Charging voltage(stage2)	V	41.8-42.5V	
10	Cut-off current(stage1→2)	A	0.3-0.7A	
11	Typical charging time	hour	Fast charge 2hours Slow charge 5hours	
12	Max.output power	W	210.0W	
13	Hold-on time	ms	NC	Input:220Vac Output:Full load
14	Ripple current	mA	300	Input:220Vac Output:Full load
15	Charge finish condition		I<0.7A	
16	LED color		Red:charging Green:finish/idle	
17	Output protect	-	OCP&OVP&Polarity error protection&Over temperature protection	
18	Efficiency	%	80%(Typical)	At max.load
Environment				
19	Operate temperature	℃	0~+40	Full load&natural convection
20	Operate humidity	%RH	20~90	Relative humidity,non-condensing.
21	Storage temperature	℃	-40~+70	
22	Storage humidity	%RH	10~95	Relative humidity,non-condensing.
23	Cooling	-	Fan force cooling only when charging	
24	Temperature factor	%	--	
25	Vibration resistance		5MM/50HZ/600S	Non-operating condition.
26	Impact resistance		1 meter drop test>=3 times	Non-operating condition.
Mechanical				
27	Weight	g	1000	
28	Size	mm	160.0*105.0*60.0	Casing only
29	Connectors	-	Defined when order	
Safety				
30	Max.temperature rise	℃	<40 on casing	At any line and Max.Load
31	Safety standards	-	CE(EN60335-2-29)	
32	EMC standard	-	CE(EN55014)	
33	MTBF	hrs	40000	
34	Limited power source	VA	-	
35	ESD	Kv	8.0	
36	Hi-Pot Insulation	v	Input to Output:3000Vac(1 min.)	For final nuit,cut-off current=10mA



**Smart Charger For
40.7V Li-ion Battery Pack**

Model: F407-040-D
Input: 180-240VAC
50-60Hz 2.0A
Output: 46.2Vdc/4.0A

LED INDICATION:
RED=Charging
Green=Charged



CAUTION:

- 1. Charge 40.7V rechargable Li-ion battery pack and capacity-4000mAh only
- 2. Indoor use only
- 3. Don't remove the cover avoid electric shock
- 4. Unplug the charger from AC outlet after use

MADE IN CHINA